

# MASTER SETTING DISC

# SERIES 525



**525-020-01**

- ◆ Hardness: HRC60-62
- ◆ Conforms to standard ASME B89.1.5

Diameter	Supplied difference	Roundness and conicity
3-21mm	±0.8µm	0.5µm
21-30mm	±0.8µm	0.7µm
30-40mm	±1.1µm	0.7µm
40-65mm	±1.5µm	1.0µm
65-110mm	±1.9µm	1.2µm
110-120mm	±1.9µm	1.6µm
120-130mm	±2.4µm	1.6µm

other sizes are available upon request

Code	Size(mm)	Code	Size(mm)	Code	Size(mm)	Code	Size(mm)	Code	Size(mm)
525-003-01	Ø3	525-016-01	Ø16	525-029-01	Ø29	525-042-01	Ø42	525-075-01	Ø75
525-004-01	Ø4	525-017-01	Ø17	525-030-01	Ø30	525-043-01	Ø43	525-080-01	Ø80
525-005-01	Ø5	525-018-01	Ø18	525-031-01	Ø31	525-044-01	Ø44	525-085-01	Ø85
525-006-01	Ø6	525-019-01	Ø19	525-032-01	Ø32	525-045-01	Ø45	525-090-01	Ø90
525-007-01	Ø7	525-020-01	Ø20	525-033-01	Ø33	525-046-01	Ø46	525-095-01	Ø95
525-008-01	Ø8	525-021-01	Ø21	525-034-01	Ø34	525-047-01	Ø47	525-100-01	Ø100
525-009-01	Ø9	525-022-01	Ø22	525-035-01	Ø35	525-048-01	Ø48	525-105-01	Ø105
525-010-01	Ø10	525-023-01	Ø23	525-036-01	Ø36	525-049-01	Ø49	525-110-01	Ø110
525-011-01	Ø11	525-024-01	Ø24	525-037-01	Ø37	525-050-01	Ø50	525-115-01	Ø115
525-012-01	Ø12	525-025-01	Ø25	525-038-01	Ø38	525-055-01	Ø55	525-120-01	Ø120
525-013-01	Ø13	525-026-01	Ø26	525-039-01	Ø39	525-060-01	Ø60	525-125-01	Ø125
525-014-01	Ø14	525-027-01	Ø27	525-040-01	Ø40	525-065-01	Ø65	525-130-01	Ø130
525-015-01	Ø15	525-028-01	Ø28	525-041-01	Ø41	525-070-01	Ø70		