

- ◆ Grade H7
- ◆ Hardness HRC 85-89
- ◆ Confirms to standard GB/T 1957-2006
- ◆ Supplied range from 1mm to 30mm, step: 1mm, other sizes or grade are available upon request

Diameter Ød (mm)	Ød1 size tolerance of Go gage (mm)	Ød2 size tolerance of Go gage (mm)	L1	L2	L
≥2 ≤3	+0.0010, +0.0022	+0.0088, +0.010	6.5	4.5	62
>3 ≤6	+0.0013, +0.0027	+0.0106, +0.012	8	6	74
>6, ≤10	+0.0015, +0.0033	+0.0132, +0.015	10	7	87
>10, ≤14	+0.0018, +0.0038	+0.0160, +0.018	12	8	99
>14, ≤18	+0.0018, +0.0038	+0.0160, +0.018	14	10	114
>18, ≤24	+0.0023, +0.0046	+0.0186, +0.021	16	12	132
>24, ≤30	+0.0023, +0.0046	+0.0186, +0.021	18	14	136

Code	Diameter Ød (mm)	Type	Code	Diameter Ød (mm)	Type	Code	Diameter Ød (mm)	Type	Code	Diameter Ød (mm)	Type
541-002-17T	2	A	541-010-17T	10	B	541-018-17T	18	B	541-026-17T	26	B
541-003-17T	3	A	541-011-17T	11	B	541-019-17T	19	B	541-027-17T	27	B
541-004-17T	4	A	541-012-17T	12	B	541-020-17T	20	B	541-028-17T	28	B
541-005-17T	5	A	541-013-17T	13	B	541-021-17T	21	B	541-029-17T	29	B
541-006-17T	6	A	541-014-17T	14	B	541-022-17T	22	B	541-030-17T	30	B
541-007-17T	7	A	541-015-17T	15	B	541-023-17T	23	B			
541-008-17T	8	A	541-016-17T	16	B	541-024-17T	24	B			
541-009-17T	9	B	541-017-17T	17	B	541-025-17T	25	B			




541-020-17T



541-006-17T

Type A



Type B

