

## ULTRASONIC THICKNESS GAUGE

### ST200



- ◆ Measure the thickness of tank, pipe and big workpiece
- ◆ LCD with backlight



Transducer PT-06 (optional)



Transducer ZT-12 (optional)



Transducer GT-12 (optional)

#### SPECIFICATION

Graduation	0.01mm(<100mm)
	0.1mm(≥100mm)
Repeatability	0.03mm(<100mm)
	0.1mm( ≥ 100mm)
Accuracy	±0.04mm (<10mm)
	±(0.04+L/1000)mm (10~100mm)
	±L/333mm ( ≥ 100mm)
	L is the thickness in mm
Velocity	1000-9999m/s
Power	3×AAA batteries
Dimension	64×116×27mm
Weight	220g

#### INCLUDED ACCESSORIES

Main unit	1pc
Transducer PT-08	1pc
AAA battery	3pcs
Couplant	1bottle
USB cable	1pc

#### OPTIONAL ACCESSORIES

Transducer	PT-06, ZT-12, GT-12
------------	---------------------

#### SPECIFICATION OF TRANSDUCERS

Code	Application	Range	Frequency	Min. pipe dimension diameter×thickness	Working temperature
PT-08	general use	0.8-300mm	5.0MHz	20×1.2mm	<60°C
PT-06	thin workpiece	0.75-40mm	7.5MHz	15×1.2mm	<60°C
ZT-12	casting steel	2-400mm	2.0MHz	30×4mm	<60°C
GT-12	high temperature	3-100mm	5.0MHz	25×3mm	<310°C

